

TRU-2000

Refraction Unit

Display your clinical excellence confidently with the TOMEY refraction unit TRU-2000. Its high functionality, combined with classic design and the comfortable chair, provide a reliable basis for all eye examinations.

Excellent features

- + Space-saving
- + Preconfigured for TOMEY equipment
- + Personal touch with internal LED light
- + Easy to install (right or left side)
- + Timeless yet innovative
- + Comfortable motorised chair with tilting action



Specifications

FEATURES	
Table	Rotating 90°, laterally movable, for 2 devices
Table height adjustment	Not available
Table lock	Magnetic
Max. load capacity (table)	50 kg
Patient chair	ER-1000
Patient chair elevation	200 mm
Max. load capacity (chair)	150 kg
Projector column height	approx. 1700 mm
Connectors	2x power outlet (230 V) 1x RS-232, 1x 6-pin (6 V / 12 V), 1x LAN, 1x USB 2.0
Reading light	White LED 12 V
Internal light	RGB LED 12 V

ELECTRIC REQUIREMENTS & WEIGHT	
Power consumption	280 VA
Power supply	110/115 V AC/230 V AC ±10 %
Total weight (incl. chair)	approx. 270 kg

DIMENSIONS	
Width	max. 1440 mm (±10 mm)
Height	max. 1750 mm (±10 mm)
Depth	max. 2360 mm (±10 mm)
Table	870 x 440 mm (±5 mm)

OPTIONAL	
Optional equipment	PA-1000 Phoropter arm "balance" PA-3000 Phoropter arm "linear" SH-1000 Skiascope/Ophthalmoscope holder TC-1000 Trial lens cabinet CBS-1000 Control box stand



TOMEY EUROPE
TOMEY GMBH

[tomey.de](https://www.tomey.de)

TOMEY GmbH is the European headquarter of TOMEY Corporation,
2-11-33 Noritakeshinmachi Nishi-Ku, Nagoya, 451-0051, Japan

2023/08 – subject to change without notice

Always read and follow the instructions for use.
Not all products, services or offers are approved or offered in every market. Please note that the current status of approval for the labelling, instructions and contents of the brochure may vary from one country to another.

